

PRINTING UNITS, DIMENSIONS AND DETAILS

EUROMAN data sheet

Equipment

Max. cylinder revolutions (1/h)	32,000/35,000 depends on cylinder circumference
Cylinder circumference (mm/inch)	1,092; 1,156; 1,196; 1,240; 1,260/43.0; 45.5; 47.1; 48.8; 49.6 depends on requirements
Max. web width (mm/inch)	965/35.4
Pages per web (A4)	32
Folder superstructure	modular system depends on requirements additional equipment depends on requirements
Folder	2:3:3, one 2 nd longitudinal fold (max. 50,000 copies per hour) option 2 nd cross fold
Webbing-up device	optional
Printing units	4 (+) option: additional printing units depends on requirements
Direction of web travel	left-right
Configurations	single-web or multiple-web depends on requirements
Drive concept	single drive technology, 1 motor per printing unit
Reel splicer	DLP 2-50, option: DLC 2100
Reel supply	MANUload – transfer table with 3m track
Plate changing system	option: PPL®
Inking unit	11-roller (3 form rollers, 3 oscillating ink rollers – tempered)
Ink fountain	lamella-type ink fountain blade
Dampening unit	4-roller turbo-dampening, option: film or spray dampening unit
Dampening water system	Baldwin Basicliner (option: technotrans)
Dryer	MEGTEC DualDry III 108, option: DualDry TNV, option: DualDry 119
Chill roller stand	5-roller, option: 6-roller
PressManagement system	option: printnet
Automation system	printnet module PECOM, option: extension levels
Support system	option: TeleSupportCenter (TSC)
ClosedLoop control systems	option, depends on requirements
Service	option: TelePresence

Some of the functions described above are options (each identified as option) and not standard equipment for the EUROMAN. They can be combined to provide customer-specific configurations in accordance with the valid options price list. The EUROMAN is subject to continuing development. Experience gained in practice and the results of research flow into product design. It is therefore in your interest that we reserve the right to make design and specification changes. Only the written order confirmation is binding. The contents of this document, in particular brand names, logos and texts, are the property of manroland and protected by law. Reproduction or utilization of this document as well as the communication of its content to others without explicit written authorization by manroland is prohibited. We may take legal measures against offenders. All rights are reserved with respect to the filing or granting of patents, utility models or designs.



If you have an Internet-capable mobile phone with a camera function, you can get further and updated information via UpCode. Use the browser of your mobile phone to go to www.upcode.fi from where you can install UpCode. Once you have installed the program aim your camera at the UpCode shown here and photograph it, or alternatively you can tap in the number series below the code. UpCode usage is free of charge; all you need to pay are the connection charges of your mobile phone services provider. You can get further information about UpCode via the code shown here or from upcode@manroland.com